

Pulse Hard Anodising

U R Rao Satellite Centre (URSC) of Indian Space Research Organisation (ISRO) has developed pulse hard anodizing process on Aluminium alloys. The hard anodic oxide coatings produced under special conditions have high hardness values and very good abrasion resistance compared to normal anodic coating. Hard anodic oxide coatings find application in the engineering industry for components where abrasion resistance is the required primary characteristic of the coating.



Salient Features

Pulse hard anodizing process is carried out at +10 °C compared to conventional hard anodizing process, which is carried out at -5 °C, thus saving a considerable cooling load. The burning and powdering problems associated with conventional hard anodizing process are eliminated.

Major Specifications

Thickness (micron)	ASTM-B-244 Eddy Current method	60±10 micron
Microhardness (HV)	ASTM-E 384, Diamond Indenter	250 - 500
Insulation value (Electrical)	10-100 V range, DC	30-1.5 GΩ

Technology Transfer

URSC-ISRO offers to transfer this Pulse Hard Anodizing Process developed by URSC to industries in India with adequate experience and facilities. Industries interested in obtaining knowhow may write giving details of their present activities, infrastructure and facilities.

Technology Transfer & Industry Coordination Division (TTID),
Programme Planning and Evaluation Group (PPEG),

📍 U R Rao Satellite Centre (URSC), ISRO, HAL Airport Road,
Vimanapura Post, Bangalore – 560 017.

✉ Email-id: tt-icd@ursc.gov.in

🌐 <https://www.ursc.gov.in/industry/index.jsp>

