



X-Band Coherent Digital TT&C Receiver

U R Rao Satellite Centre (URSC) of Indian Space Research Organisation (ISRO) has developed X-Band Coherent Digital TT&C Receiver. It uses novel implementation technique for BPSK demodulation which can support multiple data rates.



Salient Features

- FPGA based digital technology for coherent TT&C receiver baseband processing.
- + Implementation of synthesizer based Local Oscillator for coherent receiver.
- Carrier acquisition algorithms with varying loop bandwidths, BPSK demodulation algorithms, PN ranging function for improved range accuracy.

Major Specifications

- + X band carrier acquisition threshold : -125 dBm
- + Auto-carrier acquisition functionality
- + Dual data rate support for commanding
 - 1. Threshold : -122 dBm at 125 bps
 - 2. Threshold : -110 dBm at 4 kbps
- + Tone ranging support for tones of up to 500 kHz
- + PN ranging support with a threshold : -110 dBm at 1 Mcps.
- + Capability to accept level commands for dynamic command data rate selection, ranging output selection/deselection, auto carrier acquisition selection/deselection.

Technology Transfer - 7

ANY PART OR IN FULL OF THIS DOCUMENT NOT TO BE COPIED / REPRODUCED / CIRCULATED WITHOUT WRITTTEN CONSENT OF URSC-ISRO.

Technology Transfer

URSC-ISRO offers to transfer this technology of X-Band Coherent Digital TT&C Receiver to industries in India with adequate experience and facilities. Industries interested in obtaining knowhow may write giving details of their present activities, infrastructure and facilities.

Technology Transfer & Industry Coordination Division (TTID), Programme Planning and Evaluation Group (PPEG),

- UR Rao Satellite Centre (URSC), ISRO, HAL Airport Road,
- Vimanapura Post, Bangalore 560 017.
- Email-id: tt-icd@ursc.gov.in
- https://www.ursc.gov.in/industry/index.jsp

Technology Transfer - 7

ANY PART OR IN FULL OF THIS DOCUMENT NOT TO BE COPIED / REPRODUCED / CIRCULATED WITHOUT WRITTTEN CONSENT OF URSC-ISRO.